

Frontal loader Serie Euro 2.0

For tractors from
35 to 240 cv



1
Every articulations
are bushed and with
glidebush



2
Automatic locking
system tractor - frontal
loader EURO 2.0



3
Multi-plug plate
"ecologic" FASTER



4
Arm integrated
support legs



5
Oval reinforced steel
tubes



6
Automatic implement
coupling "EURO"



7
Shock absorber
(optional)



8
Integrated parallelogram
system



9
Optimum visibility
system



serie
Euro 2.0


EURO 2.0



(mm)

| | A | B | C | D | E | F | G | H | I | J |
|----------------|-------|-------|-------|-------|-----|-----|-----|-----|-------|-----|
| 320F Euro 2.0 | 3.200 | 2.990 | 2.325 | 3.735 | 130 | 380 | 60° | 50° | 1.450 | 68° |
| 340EF Euro 2.0 | 3.400 | 3.190 | 2.530 | 3.970 | 140 | 450 | 57° | 52° | 1.450 | 71° |
| 370E Euro 2.0 | 3.700 | 3.480 | 2.740 | 4.300 | 150 | 575 | 53° | 50° | 1.500 | 72° |
| 385E Euro 2.0 | 3.850 | 3.640 | 2.930 | 4.450 | 160 | 500 | 56° | 51° | 1.750 | 68° |
| 410E Euro 2.0 | 4.100 | 3.890 | 3.180 | 4.750 | 160 | 500 | 56° | 50° | 1.900 | 70° |
| 430E Euro 2.0 | 4.350 | 4.150 | 3.350 | 5.050 | 160 | 450 | 63° | 50° | 1.950 | 59° |
| 470E Euro 2.0 | 4.700 | 4.500 | 3.750 | 5.350 | 165 | 700 | 62° | 50° | 2.050 | 60° |

seconds



| | kg | | |
|----------------|-------|-------|-------|
| | 1 | 2 | 3 |
| 320F Euro 2.0 | 1.350 | 1.000 | 900 |
| 340EF Euro 2.0 | 1.600 | 1.200 | 1.050 |
| 370E Euro 2.0 | 2.130 | 1.500 | 1.250 |
| 385E Euro 2.0 | 2.800 | 2.100 | 1.700 |
| 410E Euro 2.0 | 2.300 | 2.000 | 1.600 |
| 430E Euro 2.0 | 2.500 | 1.900 | 1.700 |
| 470E Euro 2.0 | 2.800 | 2.090 | 1.950 |



| | seconds | | | |
|----------------|---------|-----|-----|-----|
| 320F Euro 2.0 | 3,7 | 2,0 | 1,6 | 2,7 |
| 340EF Euro 2.0 | 4,4 | 2,5 | 2,0 | 3,0 |
| 370E Euro 2.0 | 4,5 | 3,0 | 1,5 | 2,5 |
| 385E Euro 2.0 | 6,0 | 4,0 | 2,5 | 3,0 |
| 410E Euro 2.0 | 6,0 | 4,0 | 2,5 | 3,0 |
| 430E Euro 2.0 | 7,0 | 4,0 | 2,3 | 3,5 |
| 470E Euro 2.0 | 6,2 | 4,1 | 2,3 | 3,4 |

Mod. 320F and 340EF Euro 2.0 Values obtained at 180 bars pressure and 50 l/min flow.

Mod. 370E - 430E Euro 2.0 Values obtained at 190 bars pressure and 60 l/min flow.

Mod. 470E Euro 2.0 Values obtained at 200 bars pressure and 80 l/min flow.



Polígono Valdeferrín 104. Apdo. 23
50600 Ejea de los Caballeros. Zaragoza
Tel. +34 976 660 258 - +34 976 660 262
Fax +34 976 660 170



info@el-leon.es
www.facebook.com/palasselleon
www.el-leon.es

ZARAGOZA DELEGATION
Vía Universitat, 6, 8ª 3ª
Tel. +34 976 558 457
50009 Zaragoza
palas@el-leon.es